

**Tel-Tru
DIGI-TEL TRANSMITTER RANGES AND OUTPUTS**

	mA Readings		4	5.6	7.2	8.8	10.4	12	13.6	15.2	16.8	18.4	20
	% Output		0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
Meter Reading	Switch Position	Range	Low					Midscale					High
4.5mA	0	-80/120F	-80	-60	-40	-20	0	20	40	60	80	100	120
5.5mA	1	-40/160F	-40	-20	0	20	40	60	80	100	120	140	160
6.5mA	2	25/125F	25	35	45	55	65	75	85	95	105	115	125
7.5mA	3	0/250F	0	25	50	75	100	125	150	175	200	225	250
8.5mA	4	-60/40C	-60	-50	-40	-30	-20	-10	0	10	20	30	40
9.5mA	5	-40/80C	-40	-28	-16	-4	8	20	32	44	56	68	80
10.5mA	6	0/120C	0	12	24	36	48	60	72	84	96	108	120
11.5mA	7	0/160C	0	16	32	48	64	80	96	112	128	144	160
12.5mA	8	-75/750F	-75	7.5	90	172.5	255	337.5	420	502.5	585	667.5	750
13.5mA	9	0/400F	0	40	80	120	160	200	240	280	320	360	400
14.5mA	A	50/550F	50	100	150	200	250	300	350	400	450	500	550
15.5mA	B	150/750F	150	210	270	330	390	450	510	570	630	690	750
16.5mA	C	-60/400C	-60	-14	32	78	124	170	216	262	308	354	400
17.5mA	D	0/250C	0	25	50	75	100	125	150	175	200	225	250
18.5mA	E	0/300C	0	30	60	90	120	150	180	210	240	270	300
19.5mA	F	-75/1200F	-75	52.5	180	307.5	435	562.5	690	817.5	945	1072.5	1200
		-60/650C	-60	11	82	153	224	295	366	437	508	579	650
% Output			0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
mA Readings			4	5.6	7.2	8.8	10.4	12	13.6	15.2	16.8	18.4	20