


TEL-TRU MANUFACTURING COMPANY

NON-CONTACT INFRARED THERMOMETERS

Tel-Fast

TEL-FAST thermometers are hand-held, battery-operated devices that safely and accurately measure temperature using non-contact infrared technology. Infrared sensors consist of optics, detector, display, and output, and can display temperature measurement in °F or °C within milliseconds. Instruments are ideal for food preparation, automotive, science, electronic, plant maintenance, construction and HVAC markets.



Tel-Fast



QTFI40P

Food Inspector I.R. with combo Infrared and Fixed Thermocouple Probe

Temperature Range	-76/932°F (-60/500°C)	IR -67/482°F (-55/250°C) TC probe -67/626°F (-55/330°C)	IR -76/932°F (-60/500°C) TC probe -67/626°F (-55/330°C)
Distance to Target Ratio	12:1	12:1	12:1
Accuracy/ Resolution	+/- 2% of reading / 0.1 (°F or °C)	+/- 1.8°F (1°C) / 0.1 (°F or °C)	+/-2% / 0.1 (°F or °C)
Ambient Oper. Temp.	32/122°F (0 - 50°C)	32/122°F (0 - 50°C)	32/122°F (0 - 50°C)
Key Features	Bright, built-in 8-point circular lasers provide easy aiming Emissivity preset at 0.95 Measures Maximum temperature during scan Select F or C Amber backlit LCD display	Excellent for food and HACCP temperature monitoring HACCP zone alerts: 40°F - 140°F (4°C - 60°C) Laser sight technology Select operating modes and adjust parameters easily Built-in K-type TC mini connector Mode: Real Time Max/Min , Lock, Food Code Zone Display Emissivity: Fixed at 0.97 Spectral Response: 8-14um (immune to steam) Low battery indication Automatic power OFF	Laser: Single Laser Bright back-lit LCD display Emissivity at 0.97 Factory calibrated to NIST standards Probe Measurements: Probe is 9.3 cm or 3.7 inches long, and it is 0.2 cm thick Low battery indication Automatic power OFF
Power	2 AAA batteries (included)	2 AAA batteries (included)	2 AAA batteries (included)
Weight/ Dimensions	9 oz. / 7.5 x 6 x 1.5"	6 oz. / 6.9 x 1.5 x 2.8"	6 oz. / 6.9 x 1.5 x 2.8"
Carrying Case	Soft case sold separately (QTC2)	Soft case sold separately (QTC1)	Soft case sold separately (QTC1)

Accessories



Type K Thermocouple Probe 50428-K







Tel-Tru Manufacturing Company

TEL-TRU 408 St. Paul St., Rochester, New York 14605 USA

Phone: 585.232.1440 • 800.232.5335 • Fax: 585.232.3857 • E-mail: info@teltru.com • Web: www.teltru.com